NSN 5305-00-415-2158

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-415-2158 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.286 inches and 0.338 inches **Fastener Length:** Between 0.893 inches and 0.925 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.104 inches and 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.505 inches and 0.525 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degrees angle, 0.082 in. Lg Material: Steel comp 302 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-415-2158

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0