NSN 5305-00-417-3137

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-417-3137 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.203 inches and 0.235 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.499 inches and 0.563 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nylon pellet in thd Material: Steel comp 302 or steel comp 303se or steel comp 304 or steel comp 316 **Material Specification:** 66 federal standard all material responses or aisi/sae assn standard all material responses **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-417-3137

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0