NSN 5305-00-418-2374

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-418-2374
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.240 inches
Fastener Length:
0.920 inches
Head Style:
Pan
Head Diameter:
0.306 inches
Head Height:
Between 0.105 inches and 0.115 inches
First Diameter From Head:
0.220 inches
Second Diameter From Head:
0.090 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.300 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.680 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
2
Material:
Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel
comp 348 or steel comp 385
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

NI/s

Unc

Shelf Life:

NSN 5305-00-418-2374

Externally Relieved Body Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0