Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-418-2374

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.240 inches

Fastener Length:

0.920 inches

Head Style:

Pan

Head Diameter:

0.306 inches

Head Height:

Between 0.105 inches and 0.115 inches

First Diameter From Head:

0.220 inches

Second Diameter From Head:

0.090 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.300 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.680 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304 or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

NI/o

Shelf Life:

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0