## NSN 5305-00-418-2514



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-418-2514 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.484 inches and 0.641 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Hole Diameter:** 0.094 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.313 inches and 0.316 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Hole Configuration Style:** Round internal hexagon **Criticality Code Justification:** Zzzy Material: Steel

**Material Specification:** 

66 federal standard single material response

## NSN 5305-00-418-2514

No Fiig: A003b0

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Reference Number Differentiating Characteristics:
Certified free from mercury contamination
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: