## NSN 5305-00-419-2958



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-419-2958 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.100 inches **Fastener Length:** Between 0.236 inches and 0.241 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.078 inches **Shoulder Diameter:** 0.1855 inches first shoulder and 0.1865 inches first shoulder **Shoulder Length:** 0.1025 inches first shoulder and 0.1055 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.125 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder **Special Features:** Axis of thd eccentric to axis of shoulder by 0.031 in. Material: Steel comp 1117 **Material Specification:** Aisi assn standard single material response **Surface Treatment:** Nickel **Surface Treatment Specification:** 20-23610 mfr ref single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-00-419-2958

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0