## NSN 5305-00-419-3180

No

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-419-3180 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.120 inches and 0.130 inches **Fastener Length:** Between 0.328 inches and 0.344 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.060 inches and 0.072 inches **First Diameter From Head:** Between 0.074 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.198 inches and 0.224 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment:** Cadmium and chromate or oxide **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification 1st treatment response and qq-p-416 type 2 cl 2 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

## NSN 5305-00-419-3180

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0