

View Online at <https://aerobasegroup.com/nsn/5305-00-419-3379>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.250 inches

**Fastener Length:**

Between 0.422 inches and 0.454 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.359 inches and 0.391 inches

**Head Height:**

Between 0.422 inches and 0.454 inches

**First Diameter From Head:**

Between 0.120 inches and 0.130 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.027 inches and 0.037 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Non-std point 0.125 in. Dia, 0.156 in. Lg, chamfer 90 degrees angle

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.