## NSN 5305-00-419-5193

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-419-5193 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.050 inches and 0.100 inches **Fastener Length:** 0.313 inches **Head Style:** Fillister **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.069 inches and 0.079 inches **First Diameter From Head:** Between 0.070 inches and 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.213 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Furnished with 1 flat washer 0.250 in. Od by 0.020 in. Thk Material: Steel comp 304 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-419-5193

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0