NSN 5305-00-419-6210

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-419-6210 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.296 inches **Fastener Length:** 0.470 inches **Head Style:** Flat chamfer **Head Diameter:** 0.3437 inches **Head Height:** 0.093 inches **First Diameter From Head:** 0.203 inches **Second Diameter From Head:** Between 0.109 inches and 0.119 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.111 inches and 0.112 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.174 inches and 0.175 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Aasl **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unc

Thread Series Designator:

-69510 fscm 07187 mfr ref single treatment response

NSN 5305-00-419-6210

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0