NSN 5305-00-420-0664

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-420-0664 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.268 inches and 0.335 inches **Fastener Length:** Between 0.590 inches and 0.637 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Vanadium **Material Specification:** Vasco jet m-a fscm 81755 mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-00-420-0664

Close Tolerance Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0