

View Online at <https://aerobasegroup.com/nsn/5305-00-421-9236>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.271 inches and 0.291 inches

**Fastener Length:**

Between 0.713 inches and 0.723 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.373 inches and 0.375 inches

**Head Height:**

Between 0.241 inches and 0.261 inches

**First Diameter From Head:**

Between 0.185 inches and 0.195 inches

**Second Diameter From Head:**

Between 0.109 inches and 0.141 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.395 inches and 0.408 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.432 inches and 0.437 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel

**Material Specification:**

Ledloy a, singer co. The business machine division mfr ref single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0