Assembled Washer Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-421-9899

| Inrea Class: 2a Thread Direction: Right-hand Thread Length: C.312 Inches Fastener Length: C.312 Inches Had Style: Head Style: Head Style: Head Height: C.034 Inches Head Height: C.034 Inches Head Height: C.034 Inches Head Height: C.034 Inches Head Height: C.034 Inches Head Height: C.236 Inches C.236 Inches C.236 Inches Hat Internal Drive Style: Store Thread Diameter: C.236 Inches Thread Diameter: C.236 Inches Thread Diameter: C.236 Inches Primary Washer Outside Diameter: C.236 Inches Primary Washer Style: Flai Internal Itelch Primary Washer Style: Flai Internal I | | | | |
|--|---------------------|---------------------|--|--|
| Nead Direction:Right-handThread Length:0.312 InchesBastener Length:0.312 InchesHead Skyle:Head Skyle:Head Neight:0.094 InchesWidth Between Flats:0.295 InchesWidth Between Flats:0.296 InchesWidth Between Flats:0.295 InchesWather Quantity:1Internal Drive Style:StolNo1Thready Qty Per Inch (tp)):40Primary Washer Outside Diameter:0.295 InchesPrimary Washer Style:Ela Internal techPrimary Washer Style:Ela Internal techPrimary Washer Style:StolStolStolStolMaterialChrister Designator:UriCadmiumThready Christer DistrictCadmiumThread Style:Flat Internal Ela InternationStolStolStolChrister Designator:UriNaChrister Designator:NaNaNaStol | Thread Class: | | | |
| Right-hand Thread Length: 0.312 Inches Fastener Length: 0.312 Inches Head Style: Haxagon Head Height: 0.034 Inches Vicht Between Flats: 0.034 Inches Vicht Between Flats: 0.250 Inches Washer Quantity: 1 Iternal Drive Style: Slot Thread Diameter: 0.138 Inches Primary Washer Cutside Diameter: 0.250 Inches Primary Washer Style: Ela Internal Entit Primary Washer Style: 1 10 Primary Washer Style: 10.31 Inches 10.32 Inches Primary Washer Style: 10.31 Inches 10.32 Inches 10.32 Inches Primary Washer Style: 13.31 Inches Primary Washer Style: 13.31 Inches 14.32 Inches 15.32 Inches 15.32 Inches 16.33 Inches 17.33 Inches 17.33 Inches 18.34 Inches 19.35 Inches 19.35 Inches 19.35 Inches 10.35 Inches 10.31 Inches 10.31 Inches 10.32 Inches 10.31 Inches 10.31 Inches 10.32 Inches 10.32 Inches 10.33 Inches 11.31 Inches 12.32 Inches 13.32 Inches 13.33 Inches | | | | |
| Thread Length:0.312 inchesFaster Length:0.312 inchesHead Siyle:Head Siyle:Head Siyle:0.941 inches0.941 inches0.941 inchesVidth Between Flats:0.250 inchesVasher Quantity:1Interad Drive Style:SlotThread Diameter:0.313 inchesPrimary Washer Outside Diameter:0.265 inchesPrimary Washer Style:Flat internal treethPrimary Washer Style:SlotPrimary Washer Style:SlotPrimary Washer Style:Flat internal treethPrimary Washer Style:SlotStorPrimary Washer Style:SlotPrimary Washer Style:SlotPrimary Washer Style:SlotPrimary Washer Style:SlotPrimary Washer Style:SlotPrimary Washer Style:SlotSlotPrimary Washer Style:SlotPrimary Washer Style:Primary Washer Style:SlotPrimary Washer Style:SlotPrimary | | : | | |
| 0.312 inchesFastener Length:0.312 inchesHead Style:Head Style:Head Height:0.094 inchesWith Between Flats:0.250 inchesWasher Quantity:1Internal Drive Style:StolStolThready Qty Per Inch (tpi):40Primary Washer Guiste Diameter:0.285 inchesPrimary Washer Style:Flat internal LenchPrimary Washer Style:Primary Washer Style:Flat internal LenchPrimary Washer Style:Flat internal LenchPrimary Washer Style:Flat internal LenchPrimary Washer Style:Flat internal LenchPrimary Washer Style:Flat internal Lench< | | | | |
| Fasteer Length: 0.312 inches Head Style: Head Style: Head Note: 0.094 inches With Between Flats: 0.250 inches Wather Quantity: 1 Internal Drive Style: Stot Thread Diameter: 0.138 inches Primary Washer Outside Diameter: 0.285 inches Primary Washer Outside Diameter: 0.285 inches Primary Washer Style: Flatiental teeth Primary Washer Material Thickness: 0.031 inches Streel | | | | |
| 0.312 inchesHead Style:HexagonHead Height:0.094 inchesWidth Between Flats:0.250 inchesWasher Quantity:1Internal Drive Style:StotOlastinchesOlastinchesPrimary Washer Outside Diameter:0.280 inchesPrimary Washer Outside Diameter:0.281 inchesPrimary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:StelCadmiumCaderiusCadmiumInterdentielPrimary Masher Designator:Outsi InchesMaterial:StelDate Trace Treatent:CadmiumInterdentielPrimary Masher Designator:UniStel Clife:NaDiatification:NaFig:Fig: | | | | |
| Head Style:HexagonHead Height:0.044 inchesWidth Edeween Flats:Vidth Edeween Flats:0.250 inchesWasher Quantity:1Internal Drive Style:StdThread Diameter:0.138 inchesThread Qty Per Inch (tpl):40Primary Washer Outside Diameter:0.255 inchesPrimary Washer Style:1Statental teachPrimary Washer Style:0.31 inchesMaterial:SteelSteelSteelSterler:CadmiumThread Series Designator:UnfSheft Life:NaDin HeitsteinNaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:NaSterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler:Sterler: <th></th> <th>:</th> <th></th> <th></th> | | : | | |
| HexagonHexagonHexad Height:0.094 inchesWidth Between Flats:0.285 inchesWasher Quantity:1Internal Drive Style:StotThread Diameter:0.138 inchesThread Yuly Per Inch (tpl):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal tecthPrimary Washer Style:StotStoreOutside Diameter:0.31 inchesGuardityPrimary Washer Style:Flat internal tecthPrimary Washer Style:Cata inchesOutside Diameter:0.31 inchesBurdier Teatenen:CadmiumThread Series Designator:UnfSheff Life:NaNaDialitarization:NaFarierState <t< th=""><th></th><th></th><th></th><th></th></t<> | | | | |
| Head Height:0.094 inchesWidth Between Flats:0.250 inchesWasher Quantity:1Internal Drive Style:SlotThread Diameter:0.138 inchesThready Oty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teathPrimary Washer Style:0.311 inches0.313 inchesBurleact Teatement:0.314 inchesBurleact Teatement:CadmiumThread Series Designator:UnfSheff Life:NaMainSindSheff Life:NaNaNaNaSheff Life:NaNaNaNaFig:Sheff Life:NaSheff Life:NaSheff Life:NaSheff Life:NaSheff Life:NaSheff Life:NaSheff Life:Sheff Life:Shef | | | | |
| 0.094 inchesWith Between Flats:0.250 inchesWasher Quantity:1Internal Drive Style:StotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Style:StotelStotelStotelPrimary Washer Material Thickness:0.031 inchesSteelStrafee Treatment:CadmiumThread Series Designator:UnfShellStrafee Treatment:NaNaInter StellStrafee Treatment:NaStellStrafee Treatment:NaStellStrafee Treatment:NaStellStrafee Treatment:NaStellStrafee Treatment:StellStrafee Treatment:StellStrafee Treatment:StellStrafee Treatment:Stell </th <th></th> <th></th> <th></th> <th></th> | | | | |
| Width Between Flats:0.250 inchesWasher Quantity:1Internal Drive Style:SlotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:16 internal teathPrimary Washer Material Thickness:0.031 inchesMaterial:SteelStrafee Treatment:CadmiumThread Series Designator:UnfShafe Life:NaPrimary Contense:NaFlaties:SteelStrafee Treatment:CadmiumThread Series Designator:UnfShafe Life:NaNaSteelSteelStrafee Treatment:NaSteel <th></th> <th></th> <th></th> <th></th> | | | | |
| 0.250 inches Washer Quantity: 1 Internal Drive Style: Stot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Primary Washer Outside Diameter: 0.285 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.031 inches Material: Steel Strades Treatment: Cadmium Thered Steles Designator: Unt Ma Unt of Measure: In In Fig: | | | | |
| Washer Quantity: 1 Internal Drive Style: Stot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Primary Washer Outside Diameter: 0.285 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.031 inches Material: Steel Sterl Gadmiun Thread Series Designator: Unf Sheff Life: N/a Did Measure: - Primary Life: N/a Steel Steel Steel Cadmiun Thread Series Designator: Unf Steel Steel Steel Did Measure: N/a Na Steel Steel Steel Steel Steel Steel Steel < | | lats: | | |
| 1 Interial Drive Style: Stot Thread Diameter: 0.138 inches Thready Oty Per Inch (tpi): 40 Primary Washer Outside Diameter: 0.285 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.031 inches Batterial Steel Strafee Treatment: Cadmiun Thread Seles Designator: Unf Stell Stell Differ: Na Diff Measure: Cadmiun Thread Seles Designator: Unf Stell Stell Stell Thread Treatment: Cadmiun Thread Seles Designator: Unf Stell Stell Life: <th></th> <th></th> <th></th> <th></th> | | | | |
| Interial Drive Style: Stot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 40 Primary Washer Outside Diameter: 0.285 inches Primary Washer Style: Flat internal teeth Primary Washer Material Thickness: 0.031 inches Steel Strafee Treatment: Cadmium Thread Series Designator: Unf Shelf Life: Na Didt Measure: Inter Construct Na Didt Measure: Inter Construct File: Na Stell Stell During Construct Information: Na During Construct Information: Na Information: Information: Information: Information: Information: Information: Information: Information: Information: | Washer Quantity | : | | |
| SlotThread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:SteelSturface Treatment:CadmiumThread Series Designator:UnfShelf Life:NaInt of Measure:Int of Measure:NaFind Series Designator:NaShelf Life:NaFind Series Designator:Int of Measure:Int of Measure:NaFind:NaStell | 1 | | | |
| Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):40Pinary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:SteelSteelCadmiumThread Series Designator:UnfSheff Life:N/aUnfSheff Life:N/aDist Of Measure:Int Of Measure: <t< th=""><th>Internal Drive St</th><th>/le:</th><th></th><th></th></t<> | Internal Drive St | /le: | | |
| 0.138 inchesThready Qty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:SteelSteelSteelCadmiumThread Series Designator:UnfShelf Life:N/aUnfShelf Life:N/aDist of Measure:FShelf Life:N/aInt of Measure:FShelf Life:NaShelf Life:Shelf Lif | | | | |
| Thready Qty Per Inch (tpi):40Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UnfShelf Life:NaDir of Measure:Formiltarization:NaFing:Fing: | Thread Diameter | : | | |
| 40Prinary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.31 inchesMaterial:0.31 inchesBaterial:SteelSurface Treatment:CadmiumThread Series Designator:UnfShelf Life:N/aDir of Measure:Fmilterization:NaFig: | 0.138 inches | | | |
| Primary Washer Outside Diameter:0.285 inchesPrimary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inches0.031 inchesMaterial:SteelSurface Treatment:CadmiumThread Series Designator:UnfShelf Life:N/aDint of Measure:-Primitarization:NoFig: | Thready Qty Per | Inch (tpi): | | |
| 0.285 inchesPrimary Washer Style:Flat internal teethFlat internal teethPrimary Washer Material Thickness:0.031 inchesMaterial:0.031 inchesSteelSurface Treatment:CadmiumCadmiumShelf Life:N/aDint Of Measure:Penilitarization:NoFig: | 40 | | | |
| Primary Washer Style:Flat internal teethPrimary Washer Material Thickness:0.031 inches0.031 inchesMaterial:SteelStrace Treatment:CadmiumCadmiumThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Primary Washer | Outside Diameter: | | |
| Flat internal teethPrimary Washer Material Thickness:0.031 inches0.031 inchesMaterial:SteelSurface Treatment:CadmiumChread Series Designator:UnfShelf Life:N/aUnit Of Measure:Denilitarization:NoFig: | 0.285 inches | | | |
| Primary Washer Material Thickness:0.031 inches0.031 inchesMaterial:SteelSurface Treatment:CadmiumCadmiumThread Series Designator:UnfShelf Life:N/aUnt Of Measure:Denilitarization:NoFig: | Primary Washer | Style: | | |
| 0.031 inches Material: Steel Surface Treatment: Cadmium Thread Series Designator: Unf Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig: | Flat internal teeth | | | |
| Material:SteelSurface Treatment:CadmiumThread Series Designator:UnfShelf Life:N/aUnt Of Measure:Demilitarization:NoFig: | Primary Washer | Material Thickness: | | |
| Steel Surface Treatment: Cadmium Cadmium Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 0.031 inches | | | |
| Surface Treatment:CadmiumThread Series Designator:UnfShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Material: | | | |
| Cadmium Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig: | Steel | | | |
| Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Surface Treatme | nt: | | |
| Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No | Cadmium | | | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Series D | signator: | | |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Unf | | | |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: | | | |
| Demilitarization: No Fiig: | N/a | | | |
| Demilitarization: No Fiig: | Unit Of Measure | 1 | | |
| No Fiig: | | | | |
| Fiig: | Demilitarization: | | | |
| | No | | | |
| A003b0 | Fiig: | | | |
| | A003b0 | | | |