Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-422-2527



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.455 inches and 0.641 inches Fastener Length: Between 0.609 inches and 0.641 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches Locking Feature: Pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.375 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type

NSN 5305-00-422-2527

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator:

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0