NSN 5305-00-422-4168

View Online at https://aerobasegroup.com/nsn/5305-00-422-4168

Thumbscrew - Page 1 of 2



Thread Class: 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.312 inches **Fastener Length:** 3.730 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.750 inches **Head Height:** 0.590 inches **First Diameter From Head:** 0.230 inches **Second Diameter From Head:** Between 0.155 inches and 0.165 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.000 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.418 inches **Point Style:** Flat **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

NSN 5305-00-422-4168

Thumbscrew - Page 2 of 2



	• •					
 ın	1+	<i>(</i>)+	N/	00	CI	ıre:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.