NSN 5305-00-425-2158

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-425-2158 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.266 inches and 0.297 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Round **Head Diameter:** Between 0.287 inches and 0.309 inches **Head Height:** Between 0.107 inches and 0.119 inches **First Diameter From Head:** Between 0.115 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.312 inches and 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-425-2158

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.