NSN 5305-00-427-0012

Thread Class:

Right-hand
Thread Length:
0.417 inches
Fastener Length:

0.500 inches **Head Style:**Hexagon

Thread Direction:

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-427-0012

Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.312 inches
Washer Quantity:
1
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
74000 pounds per square inch
Hardness Rating:
80.0 rockwell b and 100.0 rockwell b
Minimum Yield Strength:
57000 pounds per square inch
Primary Washer Outside Diameter:
Between 0.395 inches and 0.410 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.020 inches and 0.025 inches
Material:
Steel
Material Specification:
Sae grade 2 assn standard single material response
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Ams2400-1 assn standard 1st treatment response or ams2402-1 assn standard 2nd treatment response

NSN 5305-00-427-0012

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0