

View Online at <https://aerobasegroup.com/nsn/5305-00-427-0029>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.400 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.190 inches

**Width Between Flats:**

Between 0.367 inches and 0.375 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

74000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b and 100.0 rockwell b

**Minimum Yield Strength:**

57000 pounds per square inch

**Primary Washer Outside Diameter:**

Between 0.494 inches and 0.510 inches

**Primary Washer Style:**

Flat external teeth

**Primary Washer Material Thickness:**

Between 0.023 inches and 0.028 inches

**Material:**

Steel

**Material Specification:**

Sae grade 2 assn standard single material response

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Ams2400-1 assn standard 1st treatment response or ams2402-1 assn standard 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0