NSN 5305-00-427-0029

Thread Class:

Right-hand **Thread Length:**0.400 inches

Thread Direction:

Fastener Length:

0.500 inches **Head Style:**

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-427-0029

Hexagon
Head Height:
Between 0.172 inches and 0.190 inches
Width Between Flats:
Between 0.367 inches and 0.375 inches
Washer Quantity:
1
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
74000 pounds per square inch
Hardness Rating:
80.0 rockwell b and 100.0 rockwell b
Minimum Yield Strength:
57000 pounds per square inch
Primary Washer Outside Diameter:
Between 0.494 inches and 0.510 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.023 inches and 0.028 inches
Material:
Steel
Material Specification:
Sae grade 2 assn standard single material response
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Ams2400-1 assn standard 1st treatment response or ams2402-1 assn standard 2nd treatment response

NSN 5305-00-427-0029

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0