NSN 5305-00-427-8686

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-427-8686

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.425 inches and 0.475 inches |
| Fastener Length: |
| Between 1.045 inches and 1.075 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.359 inches and 0.385 inches |
| Grip Diameter: |
| Between 0.1880 inches and 0.1890 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.600 inches and 0.620 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 130000 pounds per square inch |
| Hardness Rating: |
| 24.0 rockwell c and 35.0 rockwell c |
| Minimum Yield Strength: |
| 85000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-00-427-8686

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

