## NSN 5305-00-431-7216

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-431-7216

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.276 inches and 0.391 inches
Fastener Length:
Between 0.359 inches and 0.391 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:
Between 0.306 inches and 0.312 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.250 inches and 0.253 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate

## NSN 5305-00-431-7216

Socket Head Cap Screw - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0