Close Tolerance Screw - Page 1 of 1





Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.352 inches and 0.402 inches	
Fastener Length:	
Between 1.487 inches and 1.517 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.412 inches and 0.439 inches	
Grip Diameter:	
Between 0.2490 inches and 0.2495 inches	
Internal Drive Style:	
Offset cruciform (torque set)	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 1.115 inches and 1.135 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
Between 59.75 degrees and 60.25 degrees	
Special Features:	
Bearing surface of head to be grooved to 0.323 in. Min 0.325 in. Maximum dia, 0.050 in. Min 0.05	5 in. Maximum from top of head
Material:	
Titanium alloy uns r54520	
Material Specification:	
Nas621, comp 6al-4v assn standard single material response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A003b0	