NSN 5305-00-431-8012

Thread Class:

Right-hand **Thread Length:**0.639 inches

Thread Direction:

Fastener Length:

0.750 inches **Head Style:**Flat countersunk

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-431-8012

Between 0.600 inches and 0.635 inches Washer Quantity: I Internal Drive Style: Slot Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Internal Drive Style: Slot Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Internal Drive Style: Slot Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Slot Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Thread Diameter: 0.312 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Minimum Yield Strength: 57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
57000 pounds per square inch Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Countersink Angle: Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Between 80.0 degrees and 82.0 degrees Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Primary Washer Outside Diameter: 0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
0.599 inches Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Primary Washer Style: Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Countersink external teeth Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Primary Washer Material Thickness: Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Between 0.023 inches and 0.028 inches Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Material: Steel Material Specification: Sae j429gr2 assn standard single material response
Steel Material Specification: Sae j429gr2 assn standard single material response
Material Specification: Sae j429gr2 assn standard single material response
Sae j429gr2 assn standard single material response
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Ams2400-1 assn standard 1st treatment response or ams2402-1 assn standard 2nd treatment response

NSN 5305-00-431-8012

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0