NSN 5305-00-432-4013

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-432-4013 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.250 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.085 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.344 inches and 0.395 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-432-4013

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0