## NSN 5305-00-432-5576



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-432-5576 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.100 inches and 0.140 inches **Fastener Length:** Between 0.220 inches and 0.225 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.235 inches and 0.245 inches **Head Height:** Between 0.025 inches and 0.035 inches **Shoulder Diameter:** 0.112 inches first shoulder and 0.117 inches first shoulder **Shoulder Length:** 0.080 inches first shoulder and 0.085 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 56 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-432-5576

Shoulder Screw - Page 2 of 2



Fiig:

A003b0