Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-433-3570

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.172 inches a	nd 0.204 inches
Fastener Length:	
Between 0.484 inches a	nd 0.516 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.256 inches a	nd 0.270 inches
Head Height:	
Between 0.087 inches a	nd 0.097 inches
First Diameter From He	ead:
Between 0.116 inches a	nd 0.118 inches
Distance From Largest	t Bearing Surface Of Head To End Of First Diameter:
Between 0.280 inches a	nd 0.344 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inch (	tpi):
32	
Min. Tensile Strength (	psi):
80000 pounds per squar	re inch
Externally Relieved Bo	dy Diameter Quantity:
1	
Material:	
Stainless steel or steel	
Material Specification:	
Qq-s-763, 300 series fee	deral specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or
18-8 assn standard 2nd	material response
Surface Treatment:	
Passivate	
Surface Treatment Spe	ecification:
Qq-p-35 federal specific	ation single treatment response
Thread Series Designa	itor:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0