Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-433-3739

Thread Class: 2a Thread Direction: Right-hand Thread Length: Between 0.266 inches and 0.296 inches Fasteer Length: Between 0.703 inches and 0.735 inches Head Style: Knutled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Height: Between 0.307 inches and 0.203 inches First Diameter From Head: Between 0.173 inches and 0.489 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.489 inches Internal Drive Style: Stort Thread Diameter: 0.112 inches Thread Quy Per Inch (tpl): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 asen standard single material response Surface Treatment: Passivate Surface T	
Thread Direction: Right-hand Thread Length: Between 0.286 inches and 0.296 inches Faster Length: Between 0.703 inches and 0.735 inches Head Syle: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Netter: Between 0.307 inches and 0.203 inches First Diameter From Head: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.407 inches and 0.408 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.408 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches 1 Material: Stel comp 303 Material Specification: Astra Staz ass standard single material response Surface Treatment Specification: Astra Staz ass standard single treatment response Thread Series Designator: Inter State	Thread Class:
Right-And Thread Length: Between 0.266 inches and 0.296 inches Faster Length: Between 0.703 inches and 0.735 inches Head Style: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Night: Between 0.307 inches and 0.203 inches First Diameter From Head: Between 0.473 inches and 0.203 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches 1 Material: Stoel comp 303 Material: Stoel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment Specification: Astm a582 assn standard single treatment response Thread Series Designator: Unc Shuft Life: Na Unc Shuft Assista Standard single treatment response Thread Series Designator: Unc <th></th>	
Tread Length: Between 0.266 inches and 0.296 inches Fastener Length: Between 0.703 inches and 0.735 inches Head Style: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Nameter: Between 0.307 inches and 0.203 inches First Diameter From Head: Between 0.407 inches and 0.203 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Heard Diameter: 0.407 inches and 0.469 inches Between 0.407 inches and 0.469 inches Thread Diameter: 0.407 inches and 0.469 inches Thread Y Per Inch (tpi): 30t Thread Seliceved Body Diameter Quantity: 1 Material: Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shef Infe: Na Unit Of Measure: <tr td=""></tr>	
Between 0.266 inches and 0.296 inches Fastener Length: Between 0.703 inches and 0.735 inches Head Style: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Height: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Thread Diameter: 0.112 inches Thready Oty Por Inch (tpi): 0 10 Externally Relieved Body Diameter Quantity: 1 Material: Store I reatment: Passivate Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Specification: Na <tr< th=""><th>-</th></tr<>	-
Fastener Length: Between 0.703 inches and 0.735 inches Head Style: Knurled no. 1 Head Dameter: Between 0.307 inches and 0.317 inches Head Height: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thready Oty Per Inch (tpt): 40 Externality Relieved Body Diameter Quantity: 1 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Strafe Specification: Astm a580 assn standard single treatment response Sheft Life: Na Unc Sheft Life: Na Did Meterial Specification: Astm a580 assn standard single treatment response Thead Specificat	
Between 0.730 inches and 0.735 inches Head Style: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Heigh: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Cty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a580 assn standard single treatment response Thread Series Designator: Na Sheft Life: Na Externalized Series Designator: Distance: Diries Sheft Life: Na <t< th=""><th>Between 0.266 inches and 0.296 inches</th></t<>	Between 0.266 inches and 0.296 inches
Head Style: Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Height: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thready Oty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Gurda Sam standard single treatment response Thread Series Designator: Intread Series Designator: Intread Series Designator: Na Unc Sheft Life: Na Externalized Series Designator: Intread Series Designator: Intread Series Designator: Intread Series Designator: </th <th>Fastener Length:</th>	Fastener Length:
Knurled no. 1 Head Diameter: Between 0.307 inches and 0.317 inches Head Heigh: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Diatace From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thread Quy Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: Na Unic Measure: Na Dirt of Measure: Dirt of Measure: Paratire Secience: Dirt of Measure: Dirt of Measure: Paratire Secience: Dirt of Measure: Dir	Between 0.703 inches and 0.735 inches
Head Diameter: Between 0.307 inches and 0.317 inches Head Heigh: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a580 assn standard single treatment response Thread Series Designator: Ince Stoff Life: Na Material Specification: Astm a580 assn standard single treatment response Thread Series Designator: Ince Stoff Life: Na Dict Measure: Stoff Life: <td>Head Style:</td>	Head Style:
Between 0.307 inches and 0.317 inches Head Height: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Gurce Thread Specification: Astm 380 assn standard single treatment response Surface Treatment Specification: Astm 380 assn standard single treatment response Shelf Life: Na Unc Shelf Life: Na Unit Of Measure: Pace Demilitarization:	Knurled no. 1
Head Height: Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Stot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Inread Series Designator: Inca Strife Treatment Specification: Astm a582 assn standard single treatment response Surface Treatment Specification: Astm a580 assn standard single treatment response Surface Treatment: Inc Naterial Specification: Astm 380 assn standard single treatment response Direct Treatment: Inc Surface Treatment Specification: Inc Dinc	Head Diameter:
Between 0.173 inches and 0.203 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 303 Material: Stel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivate Murei Inc Strie Comp Supprise Designator: Inc Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Inc Surface Treatment: Inc Surface Treatment: Inc Surface Treatment: Inc Surf	Between 0.307 inches and 0.317 inches
First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpl): 40 Externally Relieved Body Diameter Quantity: 1 Steel comp 303 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shell Life: N/a Unc Shell Life: N/a Dirt Of Measure: Image: Dirt Of Measure: Image: Image: <	Head Height:
Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assm standard single material response Surface Treatment: Passivate Surface Treatment: Passivate Chread Specification: Astm a380 assm standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	Between 0.173 inches and 0.203 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment: Passivate Dirface Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	First Diameter From Head:
Between 0.407 inches and 0.469 inches Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shel Life: N/a Unit Of Measure: - Demilitarization:	Between 0.073 inches and 0.083 inches
Internal Drive Style: Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Sheff Life: N/a Unit Of Measure: - Demilitarization:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Slot Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Dinc of Measure: Demilitarization:	Between 0.407 inches and 0.469 inches
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Dinc Of Measure: Demilitarization:	Internal Drive Style:
0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demiltarization:	Slot
Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Thread Diameter:
40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Dit of Measure: 	0.112 inches
Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Denilitarization:	Thready Qty Per Inch (tpi):
1 Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	40
Material: Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Externally Relieved Body Diameter Quantity:
Steel comp 303 Material Specification: Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	1
Material Specification:Astm a582 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Astm a380 assn standard single treatment responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:	Material:
Astm a582 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Steel comp 303
Surface Treatment: Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Material Specification:
Passivate Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Astm a582 assn standard single material response
Surface Treatment Specification: Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Surface Treatment:
Astm a380 assn standard single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Passivate
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment Specification:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Astm a380 assn standard single treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization:	Unc
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No

NSN 5305-00-433-3739

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

