NSN 5305-00-433-8707

Fiig: A003b0

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-433-8707 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.094 inches and 0.125 inches |
| Fastener Length: |
| Between 0.344 inches and 0.375 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.155 inches and 0.167 inches |
| Head Height: |
| Between 0.045 inches and 0.053 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.086 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Material: |
| Steel |
| Material Specification: |
| Qq-s-634 federal specification single material response or qq-s-630 federal specification single material response or qq-s-631 federal |
| specification single material response or qq-s-637 federal specification single material response or qq-w-405 federal specification single |
| material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416 type 2 class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |