## NSN 5305-00-433-9163

Shoulder Screw - Page 1 of 2

За



View Online at https://aerobasegroup.com/nsn/5305-00-433-9163

Thread Class:

| Thread Direction:   |
|---|
| Right-hand  |
| Thread Length:  |
| Between 0.442 inches and 0.509 inches                       |
| Fastener Length:  |
| Between 0.952 inches and 0.999 inches                       |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.502 inches and 0.507 inches                       |
| Shoulder Diameter:  |
| 0.264 inches first shoulder and 0.265 inches first shoulder |
| Shoulder Length:  |
| 0.389 inches first shoulder and 0.411 inches first shoulder |
| Internal Drive Style:                                       |
| High-torque   |
| Thread Diameter:  |
| 0.250 inches  |
| Thready Qty Per Inch (tpi):                                 |
| 28  |
| Countersink Angle:  |
| 100.0 degrees   |
| Shoulder Shape:   |
| Round first shoulder  |
| Special Features:   |
| Furnished with 1 o-ring                                     |
| Material:   |
| Steel   |
| Material Specification:                                     |
| 3-52, fscm 76301 mfr ref single material response           |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:                            |
| 3-52, fscm 76301 mfr ref single treatment response          |
| Thread Series Designator:                                   |
| Unf   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
|   |

## NSN 5305-00-433-9163

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0