## NSN 5305-00-434-4955

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-434-4955 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.216 inches and 0.266 inches **Fastener Length:** Between 0.234 inches and 0.266 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-00-434-4955

Socket Head Cap Screw - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0