NSN 5305-00-434-5074

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-434-5074

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.422 inches and 0.516 inches Fastener Length: Between 0.484 inches and 0.516 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches Head Height: Between 0.159 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Thread Direction:Right-handThread Length:Between 0.422 inches and 0.516 inchesFastener Length:Between 0.484 inches and 0.516 inchesHead Style:Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Right-handThread Length:Between 0.422 inches and 0.516 inchesFastener Length:Between 0.484 inches and 0.516 inchesHead Style:Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinnum Yield Strength:155000 pounds per square inchMaterial:Steel
Thread Length:Between 0.422 inches and 0.516 inchesFastener Length:Between 0.484 inches and 0.516 inchesHead Style:Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.59 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Between 0.422 inches and 0.516 inches Fastener Length: Between 0.484 inches and 0.516 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Fastener Length:Between 0.484 inches and 0.516 inchesHead Style:Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Between 0.484 inches and 0.516 inches Head Style: Flat chamfer Head Diameter: Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Head Style:Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Flat chamferHead Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Head Diameter:Between 0.262 inches and 0.270 inchesHead Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Between 0.262 inches and 0.270 inches Head Height: Between 0.159 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Head Height:Between 0.159 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inchesWidth Across Flats:Between 0.140 inches and 0.142 inchesThready Qty Per Inch (tpi):32Min. Tensile Strength (psi):180000 pounds per square inchHardness Rating:38.0 rockwell c and 45.0 rockwell cMinimum Yield Strength:155000 pounds per square inchMaterial:Steel
Between 0.159 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c_and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c_and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material:
Hexagon Thread Diameter: 0.164 inches Uidth Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Thread Diameter: 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
 Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel
Minimum Yield Strength: 155000 pounds per square inch Material: Steel
155000 pounds per square inch Material: Steel
Material: Steel
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
-

NSN 5305-00-434-5074

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

