NSN 5305-00-434-6879

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-434-6879 **Thread Class:** 2a Thread Length: 0.156 inches Fastener Length: 0.281 inches **Head Style:** Flat chamfer **Head Diameter:** 0.250 inches **Head Height:** 0.125 inches **First Diameter From Head:** Between 0.093 inches and 0.099 inches **Second Diameter From Head:** Between 0.1235 inches and 0.1245 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.112 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.125 inches and 0.127 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Special Features:** Thd undercut Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-434-6879

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.