NSN 5305-00-436-1899

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-436-1899 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.180 inches and 0.220 inches **Fastener Length:** Between 0.480 inches and 0.520 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.098 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.280 inches and 0.320 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** 82 degrees cone point Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-436-1899

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0