NSN 5305-00-436-7216

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-436-7216

view Online at https://aerobasegroup.com/nsn/5305-00-436-7216
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.280 inches and 0.361 inches
Fastener Length:
Between 0.487 inches and 0.527 inches
Head Style:
Pan
Head Diameter:
Between 0.464 inches and 0.493 inches
Head Height:
Between 0.133 inches and 0.150 inches
Shoulder Diameter:
0.246 inches first shoulder and 0.249 inches first shoulder
Shoulder Length:
0.135 inches first shoulder and 0.145 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 8630 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-436-7216

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0