

View Online at <https://aerobasegroup.com/nsn/5305-00-436-7235>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.938 inches

Fastener Length:

Between 1.188 inches and 1.250 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.163 inches

Width Between Flats:

Between 0.428 inches and 0.438 inches

Hole Diameter:

0.062 inches

Thread Diameter:

0.250 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

70000 pounds per square inch

Hole Configuration Style:

Hexagon flats

Material:

Steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 420f or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style

Departure From Cited Designator:

As modified by pacs aajc, matl and abbc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0