NSN 5305-00-436-7732

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-436-7732 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.802 inches and 0.854 inches **Fastener Length:** Between 3.437 inches and 3.469 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.8844 inches and 2.0501 inches **Grip Diameter:** Between 0.9971 inches and 0.9985 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 1.000 inches **Grip Length:** Between 2.615 inches and 2.635 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-436-7732

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0