NSN 5305-00-436-9512

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-436-9512 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.221 inches and 0.241 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Fillister **Head Diameter:** Between 0.480 inches and 0.500 inches **Head Height:** Between 0.160 inches and 0.180 inches **First Diameter From Head:** Between 0.330 inches and 0.335 inches **Second Diameter From Head:** 0.203 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.259 inches and 0.279 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:** Qq-s-634, fs1010 to fs1020 federal specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-436-9512

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0