NSN 5305-00-438-4029

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-438-4029 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.300 inches **Fastener Length:** Between 1.310 inches and 1.330 inches **Head Style:** Fillister extended washer **Head Diameter:** Between 0.340 inches and 0.360 inches **Head Height:** Between 0.183 inches and 0.196 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Hole Diameter:** 0.047 inches First Diameter From Head: Between 0.095 inches and 0.105 inches **Second Diameter From Head:** Between 0.252 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.690 inches and 0.710 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.813 inches and 0.817 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style:**

Externally Relieved Body Diameter Quantity:

NSN 5305-00-438-4029

Externally Relieved Body Screw - Page 2 of 2



| Material: |
|-----------|
|-----------|

Stainless steel

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0