NSN 5305-00-442-6932

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-442-6932 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.687 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.312 inches **Head Height:** 0.125 inches **First Diameter From Head:** Between 0.182 inches and 0.192 inches **Second Diameter From Head:** Between 0.088 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.057 inches and 0.067 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.478 inches and 0.520 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-442-6932

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0