NSN 5305-00-443-2577



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-443-2577 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.342 inches and 0.392 inches **Fastener Length:** Between 0.862 inches and 0.902 inches **Head Style:** Pan **Head Diameter:** Between 0.361 inches and 0.385 inches **Head Height:** Between 0.103 inches and 0.118 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.189 inches first shoulder **Shoulder Length:** 0.510 inches first shoulder and 0.520 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 8630 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-443-2577

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0