NSN 5305-00-443-2579

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-443-2579

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.823 inches and 0.853 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp e4340 or steel comp 4037
Screw Material Specification:
Mil-s-5000 military specification 1st material response or ams 6300 assn standard 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A500d0

NSN 5305-00-443-2579

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.