NSN 5305-00-443-2638

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-443-2638 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.157 inches and 0.207 inches **Fastener Length:** Between 0.407 inches and 0.437 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.230 inches and 0.250 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-e-13924 cl 4 black military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-443-2638

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-e-13924 spec.