NSN 5305-00-443-6766

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-443-6766 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.949 inches and 1.979 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4037 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-00-443-6766

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.