

View Online at <https://aerobasegroup.com/nsn/5305-00-444-0924>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.255 inches and 0.278 inches

Fastener Length:

Between 0.713 inches and 0.723 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.373 inches and 0.375 inches

Head Height:

Between 0.241 inches and 0.261 inches

First Diameter From Head:

Between 0.2485 inches and 0.2495 inches

Second Diameter From Head:

Between 0.185 inches and 0.195 inches

Third Diameter From Head:

Between 0.109 inches and 0.141 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.084 inches and 0.087 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.398 inches and 0.408 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.445 inches and 0.458 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

3

Material:

Steel

Material Specification:

Ledloy a, singer co. The business machine div. Mfr ref single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0