NSN 5305-00-444-4657

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-444-4657 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.344 inches and 0.354 inches **Fastener Length:** Between 0.420 inches and 0.460 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.040 inches and 0.060 inches **First Diameter From Head:** Between 0.159 inches and 0.169 inches **Second Diameter From Head:** 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.015 inches and 0.025 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.055 inches and 0.065 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-444-4657

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0