

View Online at <https://aerobasegroup.com/nsn/5305-00-445-5316>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.190 inches and 0.200 inches

Fastener Length:

Between 0.870 inches and 0.880 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.240 inches and 0.260 inches

Head Height:

Between 0.180 inches and 0.200 inches

Shank Unthreaded Hole Diameter:

0.062 inches first hole and 0.065 inches first hole

First Diameter From Head:

Between 0.102 inches and 0.112 inches

Second Diameter From Head:

Between 0.065 inches and 0.085 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.608 inches and 0.626 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.670 inches and 0.690 inches

Internal Drive Style:

Slot

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.550 inches first hole and 0.570 inches first hole

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 303

Material Specification:

Qq-s-764 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.