## NSN 5305-00-445-7247

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-445-7247 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.340 inches **Fastener Length:** Between 1.610 inches and 1.650 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.308 inches and 0.318 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.182 inches and 0.192 inches **Second Diameter From Head:** Between 0.308 inches and 0.318 inches **Third Diameter From Head:** Between 0.179 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.125 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.230 inches and 1.270 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 1.310 inches and 1.320 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-445-7247

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0