Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-445-7247

Thread Class
Thread Class:
2a Thread Direction
Thread Direction:
Right-hand
Thread Length:
Between 0.290 inches and 0.340 inches
Fastener Length:
Between 1.610 inches and 1.650 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.308 inches and 0.318 inches
Head Height:
Between 0.240 inches and 0.260 inches
First Diameter From Head:
Between 0.182 inches and 0.192 inches
Second Diameter From Head:
Between 0.308 inches and 0.318 inches
Third Diameter From Head:
Between 0.179 inches and 0.185 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.125 inches and 0.140 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 1.230 inches and 1.270 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
Between 1.310 inches and 1.320 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
3
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0