NSN 5305-00-445-8750

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-445-8750 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.280 inches **Fastener Length:** Between 0.630 inches and 0.690 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.302 inches and 0.322 inches **Head Height:** Between 0.160 inches and 0.210 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.350 inches and 0.410 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 82.0 degree angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-445-8750

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0