NSN 5305-00-445-8771

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-445-8771 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.658 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Special Features:** Finish color black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:**

Unc

Specification Or Standard:

6 type

NSN 5305-00-445-8771

Socket Head Cap Screw - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| J | |

Shelf Life:

Mil-std (military Standard): Mil-c-13924 spec.